



ENLARGED VIEW OF
SHAFT EXTENSION

NOTE: -
 TERMINAL BOX CAN BE TOP OR RIGHT
 HAND SIDE MOUNTED BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
HP	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.		Kg.
INSULATION CLASS		
TEMPERATURE RISE		°C
DESIGN AMBIENT TEMPERATURE		°C
HEATER WATTS & VOLTS		WATTS, VOLTS

REMARKS

BROOK CROMPTON
PRELIMINARY

Large Industrial Motors
Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES



BROOK CROMPTON

Large Industrial Motors
GUISELEY, LEEDS, LS20 9NZ.

NOTE 1
 * ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
 PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
 INTENTION TO USE RIGID COUPLINGS AND DRIVEN
 MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/D FLANGE MOUNTED INCH A. C. MOTOR
 TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.
 FITTED WITH SIDE MOUNTED TERMINAL BOX
 FRAME SIZE :- W-DF504Z-N (4 POLE UP)

SCALE	1:10	DATE	DRG. No.
DRAWN	B. J. T.	9.2.94	M9524
CHECKED	B. J. T.	9.2.94	
APPROVED	I. J. W.	9.2.94	
REVISION:		DATE	