


NOTE: -
 TERMINAL BOX CAN BE SIDE MOUNTED
 (LEFT OR RIGHT) BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
kw	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.		Kg.
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		WATTS, VOLTS

REMARKS

ALL DIMENSIONS IN MILLIMETRES



FIRST ANGLE
 PROJECTION

**BROOK
 CROMPTON**

OUTLINE DIMENSIONS OF STD. FOOT MOUNTED METRIC A. C. MOTOR
 TOTALLY ENCLOSED FAN VENTILATED.
 FRAME SIZE : - WP-DF250M (2 POLE)

DRAWN		
CHECKED		
APPROVED		

REVISION:		DATE	
-----------	--	------	--