


NOTE: -  
 TERMINAL BOX CAN BE SIDE MOUNTED  
 (LEFT OR RIGHT) BY REFITTING FEET  
 90° IN APPROPRIATE DIRECTION.  
 CABLE ENTRY CAN BE SUPPLIED IN  
 ANY ONE OF FOUR POSITIONS AT  
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
kW	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.		Kg.
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		
WATTS,		VOLTS

REMARKS	
 <p>Large Industrial Motors Guiseley, LEEDS LS20 9NZ.</p>	

ALL DIMENSIONS IN MILLIMETRES



**BROOK CROMPTON**

NOTE !  
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST  
 PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR  
 INTENTION TO USE RIGID COUPLINGS AND DRIVEN  
 MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/FLANGE MOUNTED METRIC  
 A. C. MOTOR TO BS. 4999 PART 141, TOTALLY ENCLOSED FAN VENTILATED  
 FRAME SIZE :- W-DF200L-H (ALL POLES)

SCALE	1:6	DATE
DRAWN	JML	18/5/92
CHECKED	JML	18/5/92
APPROVED	IJW	18/5/92

DRG. No.	M8785		
REVISION:	B	M. E	DATE 30. 10. 97